

Thermotrax
Heated Laser Scanner Holder

1650 Dove Court, Marietta, Georgia 30064 USA Phone: 770.499.9420 Toll Free: 888.499.9420 www.jlcsolutions.com



JLC Solutions is proud to offer the latest generation of the **Thermotrax** heated laser scanner holder. This heater incorporates the thermostatically controlled heating elements that JLC has used successfully for nearly 20 years along with new advanced circuitry. The ABS housing with the fully adjustable anodized aluminum mounting bracket will withstand years of heavy industrial use. The **Thermotrax** heater is available in 12, 24, 36/48 volt models and is now custom-fitted for the Datalogic 9600 series laser scanners.

Thermotrax eliminates “Fogging” and “Condensation” on laser scanner lens due to temperature and humidity changes. **Thermotrax** was originally designed and built for the rugged refrigerated / freezer warehouse industry. The thermostatically controlled heated holder has proven itself as a reliable solution to the issues of hand held laser scanning. Lenses fogging and freezing, scratched lenses, damaged and destroyed scanners, these are all expensive problems that are minimized if not completely eliminated with **Thermotrax** heated laser scanner holders.

In any type of application where the lens is likely to develop condensation, the laser scanner will be rendered virtually useless without protection. It is in exactly this type of environment, with the scanner gun moving back and forth from -25°F to $+110^{\circ}\text{F}$, that **Thermotrax** was developed and tested.

Thermotrax will insure “good reads” in the harsh environments where rapid or extreme temperature changes occur such as traveling from a refrigerated or frozen storage area to a loading dock, from an air-conditioned warehouse to outdoors, or any place where condensation is likely to occur on the scanner lens.

Thermotrax comes with an integrated cable management system. This unique system draws the scanner’s cable back to the holder. The **Thermotrax** cable management system virtually eliminates the need to buy replacement cables due to over extending (repeated stretching beyond the limit of the cable length) and failures due to cable cuts and broken connection ends.

Product Specifications
Thermotrax
Heated Laser Scanner Holder

Thermotrax will protect your investment and save expensive repairs by preventing lens fogging, condensation inside the scanner and protect the scanner cable while securing the scanner itself from damage.

Part Number	Description	Compatibility
520-12-D3	Heated Scanner Holder, 12 Volt	Datalogics 9600 Series
520-24-D3	Heated Scanner Holder, 24 Volt	Datalogics 9600 Series
520-3648-D3	Heated Scanner Holder, 36-48 Volt	Datalogics 9600 Series

Mechanical

Dimensions	8 3/4 x 5 x 4 1/2" 22.2 x 12.7 x 11.2 cm	
Mounting	Includes adjustable mounting bracket	
Cable Retractor	Length	Maximum Draw 10'
	Strength	50 lbs.
	Tension	Recoil 3.75 lbs.

Environmental

Dust and Water			
Dust	Dust will not interfere with the product.		
Water	Water splashed against the enclosure from any direction shall have no harmful effect.		
Temperature Rating	Storage	-40F - +160F	-38C - +71C
	Operating	-25F - +120F	-31C - +49C
Fixed Mount Shock Rating	10 G		

Specifications are subject to change without notice

Thermotrax
Heated Laser Scanner Holder
Product Specifications

Electrical																																	
RoHS Compliant	REACH Compliant																																
Operating Voltage	12 - 48 Volt DC																																
Polarity	Independent, protected from reverse installations Overtemp protection fused at 250F (121C)																																
Indicators	Power On Green LED Heater On Red LED																																
Operating Current	With Heater On: <table border="0" style="margin-left: 20px;"> <tr> <td></td> <td style="text-align: center;"><u>24V</u></td> <td style="text-align: center;"><u>36V</u></td> <td style="text-align: center;"><u>48V</u></td> </tr> <tr> <td>Amps</td> <td style="text-align: center;">1.6</td> <td style="text-align: center;">.76</td> <td style="text-align: center;">1.02</td> </tr> <tr> <td>Temp On</td> <td style="text-align: center;">140F</td> <td style="text-align: center;">140F</td> <td style="text-align: center;">140F</td> </tr> <tr> <td></td> <td style="text-align: center;">60C</td> <td style="text-align: center;">60C</td> <td style="text-align: center;">60C</td> </tr> </table> With Heater Off: <table border="0" style="margin-left: 20px;"> <tr> <td></td> <td style="text-align: center;"><u>24V</u></td> <td style="text-align: center;"><u>36V</u></td> <td style="text-align: center;"><u>48V</u></td> </tr> <tr> <td>Amps</td> <td style="text-align: center;">.1</td> <td style="text-align: center;">.1</td> <td style="text-align: center;">.1</td> </tr> <tr> <td>Temps Off</td> <td style="text-align: center;">165F</td> <td style="text-align: center;">165F</td> <td style="text-align: center;">165F</td> </tr> <tr> <td></td> <td style="text-align: center;">74C</td> <td style="text-align: center;">74C</td> <td style="text-align: center;">74C</td> </tr> </table>		<u>24V</u>	<u>36V</u>	<u>48V</u>	Amps	1.6	.76	1.02	Temp On	140F	140F	140F		60C	60C	60C		<u>24V</u>	<u>36V</u>	<u>48V</u>	Amps	.1	.1	.1	Temps Off	165F	165F	165F		74C	74C	74C
	<u>24V</u>	<u>36V</u>	<u>48V</u>																														
Amps	1.6	.76	1.02																														
Temp On	140F	140F	140F																														
	60C	60C	60C																														
	<u>24V</u>	<u>36V</u>	<u>48V</u>																														
Amps	.1	.1	.1																														
Temps Off	165F	165F	165F																														
	74C	74C	74C																														

Warranty	
Standard	The factory warranty is one (1) year limited parts and labor.

Specifications are subject to change without